



MODEL	rpm / Hz	VOLTAGE	PRIME <sup>(1)</sup>	STANDBY <sup>(2)</sup>
PI 269P	1800 / 60	480 / 277	245 kVA / 196 kW <sub>e</sub>	269 kVA / 215.2 kW <sub>e</sub>

### ENGINE SPECIFICATIONS

Rated Output (PRP) <sup>(1)</sup>	216.6 kW <sub>m</sub>
Rated Output (ESP) <sup>(2)</sup>	238.6 kW <sub>m</sub>
Engine Make & Model	Perkins 1206A-E70TTAG1
No. of Cylinders	6 Vertical In-line
Cycle	4 Strokes
Aspiration	Turbocharged Aftercooled
Cooling Method	Water cooling
Governing Type	Electronic
Governing Class	G2 - ISO 8528 Part 1
Compression Ratio	15.8:1
Displacement	7.01 L (427.78 in <sup>3</sup> )
BorexStroke (mm/in)	105x135 / 4.13x5.3
Battery and Charger Alternator	12 VDC , 100 Amp

### AIR SYSTEM

Air Filter Type	Dry Element
Combustion Air Flow (PRP)	13.5 m <sup>3</sup> /min
Combustion Air Flow (ESP)	14.1 m <sup>3</sup> /min
Radiator Air Flow	5.62 m <sup>3</sup> /sec

### COOLING SYSTEM

Total Coolant Capacity (L)	25 L (6.6 US gal)
Water Pump Type	Centrifugal Eng-Driven
Radiator Fan Load	15 kW
Heat Radiation to Room (PRP)	128.8 kW
Heat Radiation to Room (ESP)	141.7 kW

### LUBRICATION SYSTEM

Oil Filter Type	Spin on full flow filter
Total Oil Capacity	16 L (4.2 US gal)
Oil Pan	13 L (3.4 US gal)
Oil Type	API-CH-4 or ACEA E5

### FUEL SYSTEM

Fuel Filter	Spin on
Recommended Fuel	Class A2 Diesel
Fuel Consumption Standby	61.1 lit/hr / 16.14 US gal/hr
Fuel Consumption 100% PRP	54.5 lit/hr / 14.40 US gal/hr
Fuel Consumption 75% PRP	40.4 lit/hr / 10.67 US gal/hr
Fuel Consumption 50% PRP	27.8 lit/hr / 7.34 US gal/hr

### EXHAUST SYSTEM

Muffler Type	Industrial Grade
Max. Back Pressure	TBD
Exhaust Gas Flow (PRP/ESP)	28.14 / 30.82 m <sup>3</sup> /min
Exhaust Gas Temperature	500.1 °C

### ALTERNATOR SPECIFICATIONS

Rated Output (Prime) <sup>(1)</sup>	255 kVA
Rated Output (Standby) <sup>(2)</sup>	275 kVA
Alternator Make & Model	Stamford UCI274H
Number of Poles	4
Number of Winding Leads	12
Type of Bearing	Single
Insulation Class / Temp Rise	H/H
Efficiency @ Rated Voltage	93.4%
Ingress Protection Rating	IP 23
Excitation System	Self Excited
AVR Model	Stamford SX 460

### ALTERNATOR OPERATING DATA

Overspeed	2250 r.p.m
Voltage Regulation	± 1.0 %
Waveform distortion	No load < 1.5%, Linear load < 5%
Radio Interface	EN 61000-6-2 & EN 61000-6-4
Cooling Air Flow	0.617 m <sup>3</sup> /sec

<sup>(1)</sup> **PRIME POWER RATING (PRP):** PRP is defined as the maximum power which a Generating set is capable of delivering continuously whilst supplying a variable electrical load when operated for an unlimited number of hours per year. The permissible average power output over 24 hours shall not exceed 70% of PRP unless otherwise agreed by RIC engine manufacturer. An overload capability of 10% of 100% of the prime rated electrical power is permitted for emergency use for a period of 1 hour within 12 hours of operation

<sup>(2)</sup> **EMERGENCY STANDBY POWER RATING (ESP):** ESP is defined as the maximum power available during a variable electrical power sequence, under the stated operation condition, for which a generating set is capable of delivering power in the event of a utility power outage or under test condition for up to 200 Hours of operation per year. The permissible average output over 24 hour of operation shall not exceed 70 % of the ESP power rating noting that no over load is permitted.



### CONTROLLER SPECIFICATIONS

Controller Make & Model	DeepSea 6120
Operation Mode	MRS / AMF (optional)
Display	Graphic Back-lit LCD (128x64) pixels
Ingress Protection Rating	IP65
Binary Inputs/Outputs	6 / 4
Analog Inputs	4
Measurement	Vac, A, Hz, kVA, kW, Vdc
Event Log	Alarms log, Hrs log
Communication	USB

### ENCLOSURE SPECIFICATIONS

Enclosure Type	Acoustic & Weather Proof
Anticorrosive Protection	
Polyester Powder Coated Galvanized Sheet	
Ingress Protection Rating	IP23
Lifting	ISO Standard Lifting
Emergency	External Emergency Push Button
Canopy RAL Color	RAL 2000
Baseframe RAL Color	RAL 9011
Noise Pressure level @ 7m	TBD dB(A)

### GENSET DIMENSIONS & WEIGHT

GENSET TYPE	Length (mm)	Width (mm)	Height (mm)	Fuel Tank Capacity (L)	Dry Weight (kg)
OPEN	2930	865	1900	435	1350
CLOSE	4200	1370	2100	435	2000

### STANDARD MECHANICAL FEATURES

Genset design provides a low noise level with an optimized performance of the ventilation and exhaust systems at 50 °C ambient temperature.

Robust structure design of Enclosure and Baseframe.

Heavy duty lifting lugs.

Multi doors for easy access & maintenance.

Ingress Protection Rating according to BS EN 60529.

Heavy Duty Baseframe with built-in tank & forklift pockets.

Industrial Grade Muffler with rain cap.

### OPTIONAL FEATURES

Advanced Controllers are available on request.

4 poles manual / Motorized Circuit breaker

Jacket water pre-heater

Static Battery Charger

Residential / Critical grade muffler

Fuel Filter / Water separator Fuel Filter

Remote Annunciator

### Application

Infrastructure, Industrial, Residential, Telecom, Defense, Mining, Agriculture

### STANDARD ELECTRICAL FEATURES

An advanced Control system is designed to provide a comprehensive protection and to monitor the parameters of generating set.

MCCB power circuit breaker.

Battery with charging alternator, cables, and tray.

Sealed harness & high resistant electrical connections.

Fast and accurate protection response.

Generating Set remote start function.

Numeric display with LED. Various languages capable.

